



# DOUBLE FLAP GATE VALVES F-Series LPTF-A Model

**The LPTF-A model is designed for budget conscious customers with low pressure applications.**

Meyer's F-Series Double Flap Gate Valve model LPTF-A with air-operated actuation, is used for simple low-pressure basic dust collection applications with maximum 30" WC pressure differentials where low cost is critical and a rotary airlock or slide gate is unwarranted.

Operating temperatures for this type of unit are normally in the 250°F range. Used under cyclones, baghouses and collection hoppers the F-Series is a low maintenance and dependable alternative.

## Features

- Counterweight operation -- Adjustable weights
- Abrasion resistant steel flaps -- Longer wear
- Carbon steel housing construction -- Standard materials for longer life
- Dutchman spool piece -- Resulting in larger capacities
- Single or double configuration -- Accommodates application needs



## Industries Where Used

Cement	Limestone
Foundry	Minerals

Wm. W. Meyer & Sons, Inc.

8261 Elmwood Avenue - Skokie, IL 60077 - Phones: (800) 963-4458 - (847) 673-0312 - Fax: (847) 673-5564  
website: [www.wwmeyer.com](http://www.wwmeyer.com) - email: [sales@wwmeyer.com](mailto:sales@wwmeyer.com)